


AEXTRA20 TILE

AMERICA

Tile Pavers
24x24

SHADE VARIATION

V1 - Uniform Appearance
Differences among pieces from the same production run are minimal.



WEAR CODE

Rated for all residential and commercial applications.

PENNSYLVANIA
BLUE



PENNSYLVANIA
GREY



GRAUSTEIN




WIND



GEA



TITANIO



PERFORMANCE DATA

THICKNESS: 20 mm

Characteristics:	Norms:	Results
Water Absorption	ASTM C373	≤ 0.5 %
Abrasion Resistance (Glazed)	ISO 10545-7	5/5
Breaking Strength	ASTM C648	≥ 3000 lbs
Dynamic Coefficient of Friction Wet	AcuTest	≥ 0.42
Dimensions	ASTM C499	Conforms
Facial Range of Thickness	ASTM C499	Conforms
Warpage (Diagonal)	ASTM C485	Conforms
Wedging	ASTM C502	Conforms
Frost Resistance	ASTM C1026	Frost Resistant
Scratch Hardness	MOHS	6

Notes:

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An
Appointment



www.tileamerica.com

STOCKED IN CT!