




AGLOW

Italian Porcelain 4x12, 12x24, 2x2 Mosaics, .8x12 Quarter Round



V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

GRIGIO

NERO



TAUPE



Aglow Bianco/Taupe 12x24 and Bianco 4x12 are rated 4 for residential and light commercial applications. Aglow Grigio/Nero 12x24 and 4x12 and Taupe 4x12 are rated 3 for residential applications.

PERFORMANCE DATA THICKNESS 10.00mm **CHARACTERISTIC NORM** RESULT ISO 10545-3 Water Absorption ≤ 0.5% Abrasion Resistance ISO 10545-7 3/4 ≥ 35 N/mm2 **Breaking Strength** ISO 10545-4 **Dimensions Range** ISO 10545-2 Conforms Frost Resistance ISO 10545-12 Frost Proof Chemical Resistance -Household Chemicals ISO 10545-13 A/LA/HA Chemical Resistance -A/LA/HA Low Concentration of Acids ISO 10545-13 Min. Class 3 Resistance to Stains ISO 10545-14 Crazing Resistance of Glazed Tiles ISO 10545-11 Min. Class 3

AcuTest

Notes:

Dynamic Coefficient of Friction

Per ANSI standart A108.02,4.3.8.2, joints on tiles longer tan 15" should not be staggered more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.



≥ 0.42

www.tileamerica.com