


BLANCO



# BOHO


Spanish Porcelain  
8x8

# TILE


## AMERICA

### SHADE VARIATION


V2 - Slight Variation  
Clearly distinguishable differences in texture and/or pattern within similar colors.




BEIGE



TAUPE



GRIS



GRAFITO



NEGRO



### WEAR CODE

Boho Blanco is rated (5) for all residential and commercial applications. All other Boho colors are rated (4) for all residential and light commercial applications.

### PERFORMANCE DATA

THICKNESS: 7.00 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	< 0.3 %
Abrasion Resistance	ISO 10545-7	4 / 5
Breaking Strength	ISO 10545-4	≥ 45 N/mm <sup>2</sup>
Dynamic Coefficient of Friction	AcuTest	> 0.42
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	GLA/GA
Chemical Resistance - Low Concentration of Acids	ISO 10545-13	GLA/GA
Thermal Shock Resistance	ISO 10545-9	Resists
Resistance to Stains	ISO 10545-14	Class 5

### Notes:

Minimum Recommended Grout Joint for Non-Rectified tiles is no less than 3/16".

Dynamic Coefficient of Friction (DCOF) is > 0.42 Wet.

Always mix 2-3 cartons at a time while installing to insure the best blend. All product images are representation only.

Variation in color and shading is to be expected. Final selection should be made from actual tile samples.

Book An Appointment



www.tileamerica.com