BLISS




# COCOON

Wood Look 8x48, 3x48 (Glee, Joy, Ease)



# SHADE VARIATION

V2 - Slight Variation Clearly distinguishable differences in texture and/or pattern within similar colors.



## **GLEE**



### WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use.

#### PERFORMANCE DATA

Thermal Shock Resistance

Characteristics:







# Norms: Results

	1 (011115)	
Water Absorption	ISO 10545-3	≤ 0.1 %
Deep Abrasion	ISO 10545-6	Conforms
Breaking Strength	ISO 10545-4	Conforms
Dynamic Coefficient of Friction	AcuTest	> 0.42
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Resistant
Chemical Resistance - Low Concentration of Acids	ISO 10545-13	Resistant
Resistance to Stains	ISO 10545-14	Cleanable

ISO 10545-9

#### EASE



#### Notes:



Per ANSI standard A108.02,4.3.82, joints on tiles longer than 15" should not be staggered more than 1/3 the length of the tile.

Minimum Recommended Grout Joint for Non-Rectified 3x18 tiles is no less than 3/16".

Book An Appointment Of the tile.

Book An Appointment Of the tiles is no less than 3/16".

Minimum Recommended Grout Joint for Rectified 8x48 tiles is no less than 1/8".

Dynamic Coefficient of Friction (DCOF) is > 0.42 Wet.



Resistant