ONCELLO

TILE

BLUE

Spanish Porcelain 8x8

AMERICA



V2 - Slight Variation Clearly distinguishable differences in texture and/or pattern within similar colors.



AZUL



Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications.

PERFORMANCE DATA

THICKNESS: 7.00 mm

WEAR CODE



SAGE

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	< 0.30
Abrasion Resistance	ISO 10545-7	4
Breaking Strength	ISO 10545-4	≥ 45 N/mm2
Dynamic Coefficient of Friction	AcuTest	> 0.42
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance		
Household Chemicals	ISO 10545-13	GLA/GA
Chemical Resistance		
Low Concentration of Acids	ISO 10545-13	GLA/GA
Resistance to Stains	ISO 10545-14	Class 5
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

Notes:



It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Always inspect materials prior to installations.

Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An