Gris

Raima



TILE

Spanish Porcelain 2x2 Mosaics, 12x24, 10x20, 2x10 Bullnose, 3x24 Bullnose

SHADE VARIATION

V3 - Moderate Variation
While the colors present on a single piece of tile will be

indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

WEAR CODE

Sizes 10x20 Rated 1 for Wall Applications only. All other sizes Rated 5 for All Residential and Commercial Applications.

PERFORMANCE DATA

THICKNESS: 9.20 mm

	ď,
	á
	š

<u>Cobre</u>

The state of the s	
The second secon	

Acero

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	< 0.15
Abrasion Resistance (Glazed)	ISO 10545-7	5/5
Breaking Strength	ISO 10545-4	50 N/mm2
Dynamic Coefficient of Friction Wet	AcuTest	0.48
Dimensions	ISO 10545-2	Conforms
Chemical Resistance	ISO 10545-13	Conforms
Thermal Shock	ISO 10545-9	Resists
Resistance to Stains	ISO 10545-14	Class 5
Frost Resistance	ASTM C1026	Frost Resistant
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resists

Notes:

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Always inspect materials prior to installations.

Always mix 2-3 cartons at a time while installing to insure the best blend.

