

EASEL

TILE

AMERICA

WHITE


Italian Porcelain
2x2 Mosaics, 12x24, 3x24 Bullnose



SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

White & Sand : Rated 5 For All Residential and Commercial Applications
Light Grey: Rated 4 for All Residential and Light Commercial Applications.

SAND



PERFORMANCE DATA

THICKNESS: 9.50 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.5
Abrasion Resistance (Glazed)	ISO 10545-7	4/5
Breaking Strength	ISO 10545-4	≥ 35 N/mm ²
Dynamic Coefficient of Friction Wet	AcuTest	≥ 0.42
Dimensions	ISO 10545-2	Conforms
Deep Abrasion	ISO 10545-6	≤ 175 mm ³
Chemical Resistance	ISO 10545-12	Conforms
Thermal Shock Resistance	ISO 10545-9	Conforms
Frost Resistance	ISO 10545-12	Frost Resistant
Resistance to Stains	ISO 10545-14	Class 5

Notes:

It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com

LIGHT GREY

