TAN


## SIMPLY MODERN Contemporary Look

TILE

SHADE VARIATION

CREME

V2 - Slight Variation Clearly distinguishable differences in texture and/or pattern within similar colors.



WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications.

**GREY** 

## PERFORMANCE DATA

2x2 Mosaic, 12x12, 12x24

THICKNESS: 8 mm

A STATE OF THE PARTY OF THE PAR	
	_
	_
	_
	_
	_
	_
	-
	_
	-
	_
	_
	-
	_
	-
	_
	_
	_
	_
	_
	-
	-
	-
	-
	-
	-
	-
	_
	-
	_
	_
	_
	_
	_
	-
	_
	_



The second secon
THE RESERVE OF THE PARTY OF THE
The state of the s



Characteristics:	Norms:	Results
Water Absorption	C373	≤ 0.1%
PEI Abrasion Resistance (Glazed)	C1027	Class 4
Breaking Strength	C648	>350 lbf
Dynamic Coefficient of Friction Wet	AcuTest	≥0.42
Static Coefficient of Friction Wet	C1028	≥0.62
Warpage (Diagonal)	C485	≤0.40%
Wedging	C502	≤0.25%
Front Resistance	C1026	No Evidence of Damage
Chemical Resistance	C650	Unafected
Scratch Hardness	MOHS	7



Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

