

MEL



CAMEL



AMENDO A



BOSQUE

Wood Look

7.75x36


TILE

AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example “that little bit of color” on one piece of tile may be the primary color on the next piece.



WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications. (i.e., restaurants, offices)

PERFORMANCE DATA

THICKNESS: 7.4 mm

Characteristics:	Norms:	Results
Water Absorption	C373-16	≤ 5%
PEI Abrasion Resistance (Glazed)	C1027-09	3
Breaking Strength	C648-04	≥275Lbf
Dynamic Coefficient of Friction Wet	A326-3	≥0.42
Wedging	C1028	± 0.5%
Frost Resistance	C1026-13	Frost Proof
Chemical Resistance	C650-04	Class A
Stain Resistance	C1378-04	Class A
Resistance to Stains	C1378-04	Class A
MOHS Hardness	C1895-20	5

Notes:

Per ANSI standard A108.02,4.3.82, joints on tiles longer than 15” should not be staggered more than 1/3 the length of the tile. Always mix 2-3 cartons at a time while installing to insure the best blend. All product images are representation only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.

Book An Appointment


www.tileamerica.com