

PEAK



INNER

Stone & Metal Look
2x2 Mosaic, 12x24


TILE

AMERICA

SHADE VARIATION

Clearly distinguishable differences in texture and/or pattern within

V2 - Slight Variation
similar colors.




SHORE



WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use.

STEAM



PERFORMANCE DATA

THICKNESS: 10 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	0.05 %
Abrasion Resistance (Glazed)	ISO 10545-7	NA
Breaking Strength	ISO 10545-7	≥ 47 N/mm ²
Dynamic Coefficient of Friction Wet	AcuTest	0.62
Dimensions	ISO 10545-2	Conforms
Chemical Resistance	ISO 10545-13	Conforms
Thermal Shock Resistance	ISO 10545-9	Conforms
Resistance to Stains	ISO 10545-14	Conforms
Frost Resistance	ISO 10545-12	Frost Resistant

LAKE



CLIFF



Notes:

Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com