

CALCATA
BIANCO



LUSTRE


Spanish Tile
3x3 Mosaic, 12x24, 24x24, 24x48

TILE AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications.

CREPUSCOLO
PEARL



PERFORMANCE DATA

THICKNESS: 9.5 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.5 %
Abrasion Resistance (Glazed)	ISO 10545-7	4/5
Breaking Strength	ISO 10545-4	≥ 35 N/mm ²
Dynamic Coefficient of Friction Wet	AcuTest	≥ 0.42
Dimensions	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Resistant
Chemical Resistance	ISO 10545-13	Conforms
Thermal Shock Resistance	ISO 10545-9	Conforms
Resistance to Stains	ISO 10545-14	Class 5
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

Notes:

Per ANSI standard A108.02,4.3.8.2, tiles longer than 15" should not be staggered more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An
Appointment



www.tileamerica.com

CREPUSCOLO
CREAM

