

QUARTZ ESSENCE

TILE

Stone Look 2x2 Mosaic, 4x24, 12x24

SHADE VARIATION




OTHER COLORS: V2 - Slight Variation Clearly distinguishable differences in texture and/or pattern within similar colors.

rences in texture and/or pattern within similar colors.

WILD: V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



Dl.

ROCKY

WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use.

PERFORMANCE DATA

Characteristics:

Characteristics:	Norms.	Results
Water Absorption	ISO 10545-3	≤ 0.1 %
Abrasion Resistance	ISO 10545-7	5
Dynamic Coefficient of Friction	AcuTest	≥ 0.42
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance Household Chemicals	ISO 10545-13	Resistant
Chemical Resistance Low Concentration of Acids	ISO 10545-13	Resistant
Thermal Shock Resistance	ISO 10545-9	Resistant
Resistance to Stains	ISO 10545-14	Cleanable





WILD



Notes:

It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.



www.tileamerica.com