WHITE

SALT CAVE TILE

Himalayan Salt Inspired 2x2 Mosaic, 2" Hexagon Mosaic, 3x10 Bullnose, 4x12, 10x30, 10x30 Razor, 12x24 AMERICA

SHADE VARIATION

BONE

V2 - Slight Variation Clearly distinguishable differences in texture and/or pattern within similar colors.



WEAR CODE

12x24 is rated 5 for all residential and commercial applications. 4x12, 10x22 and 10x30 are rated 1 for walls only.

PERFORMANCE DATA

THICKNESS: 9 mm

GREY				
			919	
			E 30 A	
	BLU	IF		
	DLU	JĽ		

CDEV

Characteristics:	Norms:	Results
Water Absorption	ASTM C373	≤ 0.5 % (Matte)
Deep Abrasion	ASTM C1243	<155 mm3 (Matte)
Abrasion Resistance	ASTM C1027	5 (Matte)
Breaking Strength	ASTM C648	≥ 1.40 kN (Matte)
Dynamic Coefficient of Friction	AcuTest	≥ 0.42 (Matte)
Thickness Dimension	ASTM C499	Complies
Facial Dimension	ASTM C499	Complies
Warpage Diagonal	ASTM C485	Complies
Wedging	ASTM C502	Complies
Frost Resistance	ASTM C1026	Frost Proof (Floor only)
Chemical Resistance	ASTM C650	GA/GLA

Notes:

Per ANSI standard A108.02, 4.3.82, joints on tiles longer than 15" should not be staggered more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

