



BEIGE



TAUPE



TORTORA



BIANCO



GRIGIO



ANTRACITE



# STAX

Cement Look  
2x2 Mosaic, 12x24, 2.75x24 Bullnose


# TILE

AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use.

PERFORMANCE DATA

THICKNESS: 10 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.5 %
PEI Abrasion Resistance (Glazed)	ISO 10545-7	5
Breaking Strength	ISO 10545-4	> 35 N/mm <sup>2</sup>
Static Coefficient of Friction Wet	C1028	0.63
Dimensions Range	ISO 10545-2	Conforms
Facial Range of Thickness	ISO 10545-2	▫ 0.5
Warpage (Diagonal)	ISO 10545-2	▫ 0.5
Wedging	ISO 10545-2	▫ 0.5
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	GA
Chemical Resistance - Household Chemicals	ISO 10545-13	GLA
Thermal Shock Resistance	IO 10545-9	Resistant
Resistance to Stains	ISO 10545-14	Class 5
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

## Notes:

Per ANSI standard A108.02, 4.3.82, joints on tiles longer than 18" should not be staggered more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com