

LIS SMOKE



MEDI SMOKE



FLOR SMOKE



PARK SMOKE



FLOR COLORS



LIS MOKA



MEDI MOKA



FLOR MOKA



PARK MOKA



ICE



SMOKE



MALT



MOKA



TAPESTRY WOOD


Wood Look
8x8, 8x48

TILE AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

8x8 - Class 3 Residential Applications. Suitable for all residential applications.
8x48 - Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use.

PERFORMANCE DATA

THICKNESS: 8x8 - 8.7mm / 8x48 - 11.2mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.5%
Deep Abrasion	ISO 10545-6	<130 mm ³ (8x48)
Abrasion Resistance	ISO 10545-7	3 / 4 / 5
Breaking Strength (8x8)	ISO 10545-4	≥ 52 N/mm ² (8x48); ≥ 46 N/mm ²
Dynamic Coefficient of Friction	AcuTest	≥ 0.60
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance		
Household Chemicals	ISO 10545-13	A/LA/HA
Chemical Resistance		
Low Concentration of Acids	ISO 10545-13	A/LA/HA
Resistance to Stains	ISO 10545-14	Class 5

Notes:

Per ANSI standard A108.02, 4.3.82, joints on tiles longer than 15" should not be staggered more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An
Appointment



www.tileamerica.com