

AVORIO



GRIGIO



BEIGE



TAUPE



ANTRACITE



# WATERED SILK

Stone Look


8x24 Lappato, 12x24 Matte & Lappato, 2x2 Mosaic Matte, 12x24 Muretto 3D Mosaic, 2.75x24 Bullnose Matte & Lappato,

# TILE AMERICA

## SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



## WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use.

## PERFORMANCE DATA

THICKNESS: 10.2 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.5%
Deep Abrasion	ISO 10545-6	< 175
PEI Abrasion Resistance (Glazed)	ISO 10545-7	5
Breaking Strength	ISO 10545-4	> 35 N/mm <sup>2</sup>
Dynamic Coefficient of Friction Wet	AcuTest	0.59 (matte only)
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Min. GB
Thermal Shock Resistance	ISO 10545-9	Resistant
Resistance to Stains	ISO 10545-14	Min. Class 3
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

### Notes:

Per ANSI standard A108.02,4.3.82, joints on tiles longer than 18" should not be staggered more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com