

WOOD ART

Wood Look
18x18


TILE

AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

Class 3 Residential Applications. Suitable for all residential applications.

PERFORMANCE DATA

THICKNESS: 8 mm

ASHBY




FOXHALL



Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.2%
Abrasion Resistance	ISO 10545-7	3
Breaking Strength	ISO 10545-4	≥ 38 N/mm ²
Dynamic Coefficient of Friction	AcuTest	> 0.42
Dimensions Range	ISO 10545-2	> 95%
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance Household Chemicals	ISO 10545-13	GA
Chemical Resistance Low Concentration of Acids	ISO 10545-13	GLA
Resistance to Stains	ISO 10545-14	Conforms

Notes:

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.



www.tileamerica.com